



SECT. A-A

주 기

1. 제품기능상 유해한 FLASH, 변형 및 WELDLINE등이 없을것.
2. 적용 TERMINAL : ST730751
3. 적용 HOUSING : MG641595
4. R/HOLDER는 본 도면과 같이 1차 LOCK'G상태로 유지, 공급할 것.

NOTE

1. MUST BE FREE OF FLASH, SINK AND IMPERFECTION THAT AFFECT FUNCTION.
2. APPLICABLE TERMINAL : ST730751
3. APPLICABLE HOUSING : MG641595
4. R/HOLDER MUST BE KEEP AND SUPPLY FIRST LOCKING CONDITION AS THIS DRAWING.

NO.	PART NO.	PART NAME	MATERIAL	COLOR
1	MG671596	050 15P PLUG HS'G	PBT	NATURAL
2	MG671597	050 15P PLUG R/HOLDER		NATURAL

GENERAL TOLERANCE (HOUSING)								USED ON
10 MAX	50 MAX	100 MAX	250 MAX	250 VR	ANGLE	ECCENT		
±0.2	±0.3	±0.55	±0.95	±1.4	±30°	0.1		



ISSUE MARK

				MATERIAL	SEE TABLE	KET KOREA ELECTRIC TERMINAL CO., LTD.
				FINISH	SEE TABLE	
				WIRE RANGE		CLASS
				INSULATION		TYPE 050
△ 사법변경 "020076"까지 도면재작성 LS				DATE	02.06.11	PART NO. MG651598
LTR	REVISION RECORD	DR	CHK	APP	DATE	SCALE 2/1
DR WK CHOI '99.05.12				CHK	5/13	PART NAME
CHK				APP	5/13	050 15P PLUG HS'G ASS'Y