





NO.	PART NO.	PART NAME	FINISH
1	MG671757	.090 II 2P PLUG HS'G (SPK)	NATURAL
2	MG671758	.090 II 2P PLUG SPACER(SPK)	YELLOW



NO.	MATERIAL	COLOR
0	P B T:	NATURAL
1		RED
2		BLUE
3		YELLOW
4		GRAY
5		BLACK
6		W/GREEN
7		BROWN
8		GREEN


GENERAL TOLERANCE (HOUSING)					USED ON
10MAX	20MAX	45MAX	ANGLE	ECCENT	
±0.2	±0.25	±0.3	±30'	0.1	

주 기

1.기능상 유해한 BURR 및 WELDLINE등이 없을것.

2.적용 CONNECTOR: MG641762

적용 TERMINAL: ST730675, 676, 677



SECTION A-A



ISSUE MARK

					MATERIAL	PBT	KET KOREA ELECTRIC TERMINAL CO., LTD.				
					FINISH	SEE TABLE					
					WIRE RANGE	CLASS .090 II					
					INSULATION	TYPE 7283-1026					
	시제품용(990505)본격 LOCK 관동용				WON	KIM	CH0	'98.12			
LTR	REVISION RECORD				DR	CHK	APP	DATE	TOLERANCE EXCEPT AS NOTED	SCALE	PART NO
DR.	WON. '98.11.23				CHK	KJ	KIM	6/09			MG651759
CHK.					APP.	JH	CHO	6/12			
										PART NAME .090 II 2P PLUG HOUSING ASS'Y(SPK)	