


NO.	PART NO.	PART NAME	MATERIAL	FINISH
1	MG671877	1809 16P PLUG HOUSING (L)	SEE TABLE	NATURAL
2	MG671004	1809 16P PLUG SPACER		NATURAL

GENERAL TOLERANCE (HOUSING)					USED ON
10MAX	20MAX	45MAX	ANGLE	ECCENT	
±0.2	±0.25	±0.3	±30'	0.1	

NO.	MATERIAL	COLOR
0	P B T	NATURAL
1		RED
2		BLUE
3		YELLOW
4		GRAY
5		BLACK
6		W/GREEN
7		BROWN
8	GREEN	



주 기

1. 외형기능상 유해한 BURR, 변형 및 WELDLINE 등이 없을것.
2. 적용 TERMINAL : ST730644,645,646 (187 TYPE : 4 EA)
ST730675,676,677 (090 TYPE : 12 EA)
3. 적용 HOUSING : MG641883 (1809 16P REC. ASS'Y(L))
4. SPACER는 본 도면과 같이 1차 LOCK'G 상태로 유지, 공급할것.

NOTE

1. MUST BE FREE OF FLASH, DISTORTION AND IMPERFECTION THAT AFFECT FUNCTION.
2. APPLICABLE TERMINAL : ST730644,645,646 (187 TYPE : 4 EA)
ST730675,676,677 (090 TYPE : 12 EA)
3. APPLICABLE HOUSING : MG641883 (1809 16P REC. ASS'Y(L))
4. SPACER MUST BE KEEP AND SUPPLY FOR FIRST LOCKING CONDITION AS THIS DRAWING.



ISSUE MARK

		MATERIAL	SEE TABLE			KETA KOREA ELECTRIC			
		FINISH	SEE TABLE			TERMINAL CO., LTD.			
		WIRE GAUGE				CLASS			
		INSULATION				TYPE			
DATE	REVISION	RECORD	DR	CHK	APP	DATE	SCALE	PART NO.	MG651881
04.09.01	93.09.01	WK	CHOI	9/1	9/1	9/1	2/1		
04.09.01	9/1	9/1	9/1	9/1	9/1	9/1	2/1		
		PART NAME		1809 16P PLUG HOUSING ASS'Y (L)					