

GENERAL TOLERANCE (HOUSING)							USED ON
10 MAX	50 MAX	100 MAX	250 MAX	250 VR	ANGLE	ECCENT	
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	


NO.	PART NO.	PART NAME	MATERIAL	FINISH
1	MG672501	1809 24P PLUG HS'G	PBT	NATURAL
2	MG672502	1809 24P PLUG SPACER	PBT	NATURAL

주 기

- 1.기능상 유해한 BURR 및 WELDLINE등이 없을것.
- 2.적용 TERMINAL : ST730675, 676, 677(.090 II)
- 적용 TERMINAL : ST730644, 645, 646(.187 II)

NOTE

1. MUST BE FREE OF FLASH, SINK AND IMPERFECTION THAT AFFECT FUNCTION.
2. APPLICABLE TERMINAL :ST730675, 676, 677(.090 II)
- APPLICABLE TERMINAL :ST730644, 645, 646(.187 II)



ISSUE MARK

MATERIAL	SEE TABLE		KOREA ELECTRIC TERMINAL CO., LTD.					
FINISH	SEE TABLE							
WIRE RANGE	CLASS .090 II + 187 II							
INSULATION	TYPE							
LTR	REVISION RECORD	DR	CHK	APP.	DATE	TERMINAL REFER TO NOTES	SCALE	PART NO.
DR.	KYM 02.09.03	CHK			9/4	SEE TABLE	2/1	MG652503
CHK.		APP.			9/4	PART NAME		1809 24P PLUG HS'G(187(4)+090(20))