





SECTION A-A



GENERAL TOLERANCE (HOUSING)					USED ON
10MAX	20MAX	45MAX	ANGLE	ECCENT	
±0.2	±0.25	±0.3	±30'	0.1	

NOTE

1. 지시없는 R는 전부0.3으로 한다.
2. 기능상 유해한 BURR,변형등이 없을것.
3. 적용 부품
 △ TERMINAL-ST740653,654,655,668,941
 R/COVER-MG632946
 W/SEAL -MG680954
4. 상대 HOUSING - MG642928

NOTE

1. UNLESS OTHERWISE SPECIFIED ALL RADIUS TO BE 0.3 RADIUS.
2. MUST BE FREE OF BURR,WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
3. APPLICABLE PART
 △ TERMINAL-ST740653,654,655,668,941
 R/COVER-MG632946
 W/SEAL -MG680954
4. COMPARE HOUSING-MG642928



NO	적용TERMINAL	ASSY/NO	PART/NO	PART/NAME	MATERIAL	FINISH
1	BRASS	MG652934-5	MG672932-5	312 II WP 2M HS'G	PBT	BLACK
2			MG672933	312 II WP 2M F/HOLDER	PBT	NATURAL
1	COPPER ALLOY	MG652934-5S	MG672932-5	312 II WP 2M HS'G	PBT	BLACK
2			MG672933-4	312 II WP 2M F/HOLDER	PBT	GRAY

						MATERIAL	SEE TABLE	KOREA ELECTRIC TERMINAL CO., LTD.	
						FINISH	SEE TABLE		
						WIRE RANGE		CLASS	
						INSULATION		TYPE	
						DATE		SCALE 1/1	
						DATE		PART NO. MG652934	
						DATE		PART NAME	
						DATE		312II WP 2M PLUG ASS'Y	