


GENERAL TOLERANCE (HOUSING)							USED ON
10MAX	50MAX	100MAX	250MAX	250VR	ANGLE	ECCENT	
±0.2	±0.3	±0.55	±0.95	±1.4	±30°	0.1	

NO.	PART NO.	PART NAME	MATERIAL	FINISH
①	MG674026	312II 1F HOUSING	PBT	NATURAL
②	MG674027	312II 1F SPACER	PBT	NATURAL

NOTE

- UNLESS OTHERWISE SPECIFIED ALL RADIUS TO BE 0.3 RADIUS.
- MUST BE FREE OF BURR, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
- APPLICABLE TERMINAL : ST730642, 643
- 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBBs, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.



ISSUE MARK

주 기

- 지시하지 않은 반경 R은 0.3 으로 한다.
- 기능상 유해한 BURR 및 WELDLINE 등이 없을것.
- 적용 TERMINAL : ST730642, 643
- 제품내 함유된 6대 유해물질 (납, 수은, 카드뮴, 6기크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.

						MATERIAL SEE TABLE		 KOREA ELECTRIC	
						FINISH SEE TABLE		TERMINAL CO., LTD.	
						WIRE RANGE		CLASS	
						INSULATION		TYPE	
LTR	REVISION RECORD		DR	CHK	APP	DATE	SCALE 2/1		PART NO. MG653994
DR.	KBS 2007.12.26		CHK.				PART NAME		312 II 1F ASSY
CHK.			APP						