



GENERAL TOLERANCE (HOUSING)									USED ON
10MAX	30MAX	50MAX	70MAX	100MAX	120MAX	250MAX	250VR	ANGLE	
±0.15	±0.20	±0.30	±0.40	±0.50	±0.75	±0.90	±1.40	±30'	

NOTE

- MUST BE FREE OF BURR, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
- APPLICABLE TERMINAL(060) : ST741340, ST741341, ST741342
 APPLICABLE TERMINAL(110) : ST741288, ST741289, ST741290
 APPLICABLE WIRE SEAL(060) : MG685389, MG685390, MG685391, MG685392, MG685393
 APPLICABLE WIRE SEAL(110) : MG680522, MG680470, MG680564
 APPLICABLE DUMMY SEAL (060) : MG685394
 APPLICABLE DUMMY SEAL (110) : MG680905
- 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBBs, PPDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.

주 기

- 기능상 유해한 BURR 및 WELDLINE 등이 없을 것.
- 적용 TERMINAL (060) : ST741340, ST741341, ST741342
 적용 TERMINAL (110) : ST741288, ST741289, ST741290
 적용 WIRE SEAL (060) : MG685389, MG685390, MG685391, MG685392, MG685393
 적용 WIRE SEAL (110) : MG680522, MG680470, MG680564
 적용 DUMMY SEAL (060) : MG685394
 적용 DUMMY SEAL (110) : MG680905
- 제품내 함유된 6대 유해물질 (납, 수은, 카드뮴, 6가크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.

APPROVED

2020-12-11

KOREA ELECTRIC
TERMINAL CO., LTD.
Korea Electric Te
rminal Co., LTD.

ISSUE MARK

NO.	PART NO.	PART NAME	MATERIAL	FINISH
①	MG675922	060110 WP 6M HOUSING	PBT+GF 10%	BLACK
②	MG675921	060110 WP 6M F/HOLDER	PBT+GF 10%	NATURAL

						MATERIAL	SEE TABLE	KOREA ELECTRIC TERMINAL CO., LTD.	
						FINISH	SEE TABLE		
②	ECO-2011-139	근거 도면 제작성	LND	KSC	CJH	2020.11.09	WIRE RANGE	CLASS	060110
①	ECO-2009-129	근거 도면 제작성	LND	KSC	CJH	2020.09.10	INSULATION	TYPE	WP
LTR	REVISION RECORD		DR.	CHK.	APP.	DATE	TOLENANCE EXCEPT AS NOTED	SCALE	2/1
DR.	SONG.Y.C	2014.07.11	CHK.				PART NAME	060110 WP 6M ASSY	
CHK.	JEONG.B.S	2014.07.11	APP.	BIN. O.I	2014.07.11				