

CU645066-5

CU656850-40

CUSTOMER DRAWING PART NO. MG645066

GENERAL TOLERANCE (HOUSING)

10MAX	30MAX	50MAX	70MAX	100MAX	120MAX	250MAX	250VVR	ANGLE	ECCENT
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1			

USED ON

NOTE

- APPLICABLE TERMINAL : ST730962, 963-3 (025)
ST730715, 716, 717-3 (187)
- APPLICABLE WIRE SEAL : MG683292, 293 (025)
MG681367, 370, 371, 372 (187)
- APPLICABLE DUMMY SEAL : MG683290 (025)
MG681373 (187)
- APPLICABLE REAR COVER : MG635605
- 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT, CHROMIUM, PBBs, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.

주 기

- 적용 TERMINAL : ST730962, 963-3 (025)
ST730715, 716, 717-3 (187)
- 적용 WIRE SEAL : MG683292, 293 (025)
MG681367, 370, 371, 372 (187)
- 적용 DUMMY SEAL : MG683290 (025), MG681373 (187)
- 적용 REAR COVER : MG635605
- 제품내 함유된 6대 유해물질 (납, 수은, 카드뮴, 6가크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.

NO.	PART NAME	PART NO.	MATERIAL	COLOR	QTY.
1	025187 HYBRID WP 8F HOUSING	MG675067-5	PBT	BLACK	1
2	025187 HYBRID WP 8F FRONT HOLDER	MG675068	PBT	NATURAL	1
3	025187 HYBRID WP 8F LEVER	MG675069	PBT+GF30	BLACK	1
4	025187 HYBRID WP 8F INNER SEAL	R602280	SILICONE	RED	1

REVISION RECORD

DR.	CHK.	APP.	DATE	REVISION
SHIN.S.H	H.K.S		2010.05.12	025187 HYBRID WP 8F ASSY
J.Y.S			05/12	

APPROVED
2019-11-05
KOREA ELECTRIC TERMINAL CO., LTD.
Korea Electric Terminal Co., Ltd.

CUSTOMER DRAWING PART NO. MG656850-40

GENERAL TOLERANCE (HOUSING)

10MAX	30MAX	50MAX	70MAX	100MAX	120MAX	250MAX	250VVR	ANGLE	ECCENT
±0.15	±0.20	±0.30	±0.40	±0.50	±0.75	±0.90	±1.4	±30'	0.1

USED ON

NOTE

- APPLICABLE TERMINAL : ST731435-3 (025)
ST731436-3 (187)
- APPLICABLE WIRE SEAL : MG683292-N (025)
MG681372 (187)
- APPLICABLE REAR COVER : MG635605
- 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT, CHROMIUM, PBBs, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.
- TEST SPECIFICATION : ES91500-00(CONNECTOR-GENERAL)
OUTSIDE OF STANDARD TEMPERATURE TEST (HIGH TEMPERATURE 150°C)

주 기

- 적용 TERMINAL : ST731435-3 (025)
ST731436-3 (187)
- 적용 WIRE SEAL : MG683292-N (025)
MG681372 (187)
- 적용 REAR COVER : MG635605
- 제품내 함유된 6대 유해물질 (납, 수은, 카드뮴, 6가크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.
- 시험 규격 : ES91500-00(커넥터 일반)
규격 외 온도 평가(고온 150°C 조건)

NO.	PART NAME	PART NO.	MATERIAL	COLOR	QTY.
1	025187 HYBRID WP 8F HOUSING	MG676607-40	HPA	D/GRAY	1
2	025187 HYBRID WP 8F FRONT HOLDER	MG676608-5	HPA	BLACK	1
3	025187 HYBRID WP 8F LEVER	MG675069	PBT+GF30	BLACK	1
4	025187 HYBRID WP 8F INNER SEAL	R603518	SILICONE	BLUE	1

REVISION RECORD

DR.	CHK.	APP.	DATE	REVISION
LKS			2016.01.18	025187 HYBRID WP 8F ASSY
LJE			2016.01.18	

APPROVED
2019-11-05
KOREA ELECTRIC TERMINAL CO., LTD.
Korea Electric Terminal Co., Ltd.