



GENERAL TOLERANCE (HOUSING)										USED ON
10 MAX	30 MAX	50 MAX	70 MAX	100 MAX	120 MAX	250 MAX	250 VR	ANGLE	ECCENT	
±0.15	±0.2	±0.3	±0.4	±0.5	±0.75	±0.9	±1.4	±30'	0.1	

주 기

1. 기능상 유해한 BURR 및 WELDLINE 등이 없을 것,
2. 적용 TERMINAL(C025) : ST731409-3, 1410-3, 1409-G, 1410-G
적용 TERMINAL(C060) : ST731411-3, 1412-3, 1413-3
적용 CONNECTOR : MG646095
적용 LEVER : MG635831-5
3. 제품내 함유된 6대 유해물질 (납, 수은, 카드뮴, 6가크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.

NO.	MATERIAL	COLOR
* 0	P B T	NATURAL
1		RED
2		BLUE
20		JADE
3		YELLOW
4		GRAY
40		DARK GRAY
41		LIGHT GRAY
5		BLACK
6		GREEN
7		BROWN
8	LIGHT GREEN	
9	MAGENTA	
11	ORANGE	

NOTE

1. MUST BE FREE OF FLASH, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION,
2. APPLICABLE TERMINAL(C025) : ST731409-3, 1410-3, 1409-G, 1410-G
APPLICABLE TERMINAL(C060) : ST731411-3, 1412-3, 1413-3
APPLICABLE CONNECTOR : MG646095
APPLICABLE LEVER : MG635831-5
3. 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBBs, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.

APPROVED

2019-11-06

KOREA ELECTRIC
TERMINAL CO., LTD.
Korea Electric Te
rminal Co., LTD.

ISSUE MARK

NO.	PART NAME	PART NO.	MATERIAL	COLOR	QTY.
1	025060 44F HOUSING	MG676871	SEE TABLE	SEE TABLE	1
2	025060 44F SPACER	MG676872-3	PBT	YELLOW	1

				MATERIAL	SEE TABLE	KOREA ELECTRIC TERMINAL CO., LTD.	
				FINISH	SEE TABLE		
				WIRE RANGE		CLASS	HYBRID
				INSULATION		TYPE	025/060
ECO-1802-356 근거 도면 변경	NSJ	HYJ	CJH	18.02.28		PART NO.	MG656928
LTR	REVISION RECORD	DR.	CHK.	APP.	DATE	TOLERANCE EXCEPT AS NOTED	SCALE 1/1
	DR. NST 2017.04.03		CHK.			PART_NAME	025060 44F ASSY
	CHK. WDH 2017.04.03			APP.	LJE 2017.04.03		