




GENERAL TOLERANCE (HOUSING)										USED ON
10 MAX	30 MAX	50 MAX	70 MAX	100 MAX	120 MAX	250 MAX	250 VR	ANGLE	ECCENT	
±0.15	±0.2	±0.3	±0.4	±0.5	±0.75	±0.9	±1.4	±30'	0.1	

- 주기
- 기능상 유해한 BURR 및 WELDLINE 등이 없을 것.
 - 적용 TERMINAL(C025) : ST731409-3, ST731410-3
적용 TERMINAL(N110) : ST731424-3, ST731425-3, ST731426-3
 - 적용 CONNECTOR : MG646115
 - 제품내 함유된 6대 유해물질 (납, 수은, 카드뮴, 6가크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.

- NOTE
- MUST BE FREE OF BURR, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION,
 - APPLICABLE TERMINAL(C025) : ST731409-3, ST731410-3
APPLICABLE TERMINAL(N110) : ST731424-3, ST731425-3, ST731426-3
 - APPLICABLE CONNECTOR : MG646115
 - 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBBs, PBDEs) SHOULD NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION



NO.	MATERIAL	COLOR
0	SEE TABLE	NATURAL
1		RED
11		ORANGE
2		BLUE
22		JADE
3		YELLOW
4		GRAY
41		LIGHT GRAY
42		DARK GRAY
5		BLACK
61	LIGHT GREEN	
62	DARK GREEN	
7	BROWN	
9	MAGENTA	

APPROVED

2019-11-06

**KOREA ELECTRIC
TERMINAL CO., LTD.
Korea Electric Te
rminal Co., LTD.**

NO	PART NO.	PART NAME	MATERIAL	FINISH	Q'TY
1	MG676953	025110 12F HOUSING	PBT	SEE TABLE	1
2	MG676954	025110 12F SPACER	PBT	LIGHT GRAY	1

ISSUE MARK

MATERIAL	SEE TABLE	KIET ENGINEERED	KOREA ELECTRIC TERMINAL CO., LTD.				
FINISH	SEE TABLE						
WIRE RANGE	-			CLASS	HYBRID		
INSULATION	-	TYPE	C025 / N110				
LTR	REVISION RECORD	DR.	CHK.	APP.	DATE	SCALE	PART NO.
DR.	LJJ 2017.06.12	CHK.	CKI	2017.06.12	SCALE	2/1	MG656949
CHK.		APP.	LJE	2017.06.12	PART-NAME		025110 12F ASSY