



GENERAL TOLERANCE (HOUSING)

10 MAX	30 MAX	50 MAX	70 MAX	100 MAX	120 MAX	250 MAX	250 VR	ANGLE	USED ON
±0,15	±0,20	±0,30	±0,40	±0,50	±0,75	±0,90	±1,40	±30'	

NO.	MATERIAL	COLOR
* 0	PBT	NATURAL
1		RED
2		BLUE
20		JADE
3		YELLOW
4		GRAY
40		DARK GRAY
41		LIGHT GRAY
5		BLACK
6		DARK GREEN
7		BROWN
8	LIGHT GREEN	
9	MAGENTA	
11	ORANGE	

주기

- 기능상 유해한 BURR 및 WELDLINE 등이 없을 것.
- 적용 TERMINAL (C025): ST731409-3, ST731410-3, △ST731542-3  
적용 TERMINAL (C060): ST731411-3, ST731412-3, ST731413-3,  
△ST731566-3, △ST731538-3, △ST731539-3  
△알루미늄 전선용 (C060): ST731487-3, ST731479-3

- 상대물 HOUSING: UNIT
- 제품내 함유된 6대 유해물질 (납, 수은, 카드뮴, 6가크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.

NOTE

- MUST BE FREE OF BURR, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
- APPLICABLE TERMINAL (C025): ST731409-3, ST731410-3, △ST731542-3  
APPLICABLE TERMINAL (C060): ST731411-3, ST731412-3, ST731413-3,  
△ST731566-3, △ST731538-3, △ST731539-3  
△FOR ALUMINIUM WIRING (C060): ST731487-3, ST731479-3

- APPLICABLE FEMALE HOUSING: UNIT
- 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBBs, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.

APPROVED

2020-12-24

KOREA ELECTRIC  
TERMINAL CO., LTD.  
Korea Electric Te  
rminal Co., LTD.

ISSUE MARK

NO.	PART NAME	PART NO.	MATERIAL	COLOR	Q'TY
1	025060 16F HOUSING	MG677002	SEE TABLE	SEE TABLE	1
2	025060 16F SPACER	MG677003-3	PBT	YELLOW	1

MATERIAL	SEE TABLE		KOREA ELECTRIC TERMINAL CO., LTD.
FINISH	SEE TABLE		
WIRE RANGE	-	CLASS	C025/C060
INSULATION	-	TYPE	비방수
LTR	REVISION RECORD	DR, CHK, APP, DATE	TOLERANCE EXCEPT AS NOTED
DR, JDR	2017, 09, 13	CHK,	SCALE 2/1
CHK,		APP, SSH	2017, 09, 15
PART_NAME		025060 16F ASSY	