



GENERAL TOLERANCE (HOUSING)										USED ON
10 MAX	30 MAX	50 MAX	70 MAX	100 MAX	120 MAX	250 MAX	250 VR	ANGLE	ECCENT	
±0.15	±0.2	±0.3	±0.4	±0.5	±0.75	±0.9	±1.4	±30'	0.1	

NO.	MATERIAL	COLOR
0	PBT	NATURAL
1		RED
* 2		BLUE
20		JADE
3		YELLOW
4		GRAY
40		DARK GRAY
* 41		LIGHT GRAY
5		BLACK
6		DARK GREEN
7		BROWN
8	LIGHT GREEN	
9	MAGENTA	
11	ORANGE	

- 주 기
- 기능상 유해한 BURR 및 WELDLINE 등이 없을 것.
 - 적용 TERMINAL(C025) : ST731409-3, ST731410-3, ST731409-G, ST731410-G
 적용 TERMINAL(N250) : ST731428-3, ST731429-3, ST731430-3
 적용 TERMINAL(375) : ST730722-3, ST730723-3
 적용 TERMINAL(FAKRA) : KR20203-20, KR20301-20, KR00406-20
 적용 CONNECTOR : MG646294 OR MG646295
 적용 LEVER : MG635946
 적용 375 REAR HOLDER : MG630660
 - 제품내 함유된 6대 유해물질 (납, 수은, 카드뮴, 6가크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.

- NOTE
- MUST BE FREE OF BURR, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
 - APPLICABLE TERMINAL(C025) : ST731409-3, ST731410-3, ST731409-G, ST731410-G
 APPLICABLE TERMINAL(N250) : ST731428-3, ST731429-3, ST731430-3
 APPLICABLE TERMINAL(375) : ST730722-3, ST730723-3
 APPLICABLE TERMINAL(FAKRA) : KR20203-20, KR20301-20, KR00406-20
 APPLICABLE CONNECTOR : MG646294 OR MG646295
 APPLICABLE LEVER : MG635946
 APPLICABLE 375 REAR HOLDER : MG630660
 - 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBBs, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.



PART LIST

NO.	PART NAME	PART NO.	MATERIAL	COLOR	QTY.
1	025250375 FAKRA 54F HOUSING	MG677414	SEE TABLE	SEE TABLE	1
2	025250375 FAKRA 54F SPACER	MG677415-3	PBT	YELLOW	1

MATERIAL	SEE TABLE	KET KOREA ELECTRIC TERMINAL CO., LTD.
FINISH	SEE TABLE	
WIRE RANGE	-	CLASS 025/250/375/FAKRA
INSULATION	-	TYPE 비방수
LTR	REVISION RECORD	SCALE 1/1
DR, LCK 2019.01.17	CHK, NDH 2019.01.17	PART NO. MG657067
CHK,	APP, CNS 2019.01.17	PART_NAME 025250375 FAKRA 54F ASSY