



GENERAL TOLERANCE (HOUSING)

10 MAX	30 MAX	50 MAX	70 MAX	100 MAX	120 MAX	250 MAX	250 VR	ANGLE	ECCENT	USED ON
±0.15	±0.2	±0.3	±0.4	±0.5	±0.75	±0.9	±1.4	±30'	0.1	

NO.	PART NAME	PART NO.	MATERIAL	COLOR	QTY.
1	025060 68F HOUSING_B	MG677771	SEE TABLE	SEE TABLE	1
2	025060 68F SPACER_B	MG677772-41	PBT	L/GRAY	1

NO.	MATERIAL	COLOR
0	P B T	NATURAL
1		RED
2		BLUE
20		JADE
3		YELLOW
4		GRAY
40		DARK GRAY
41		LIGHT GRAY
5		BLACK
6		GREEN
7		BROWN
8	LIGHT GREEN	
9	MAGENTA	
11	ORANGE	

- NOTE**
- MUST BE FREE OF FLASH, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
 - APPLICABLE TERMINAL(02511) ; ST731374-3,ST731375-3
APPLICABLE TERMINAL(C060) ; ST731411-3,ST731412-3,ST731413-3
APPLICABLE CONNECTOR ; MG645941
APPLICABLE LEVER; 635752-5
 - 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBBs, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.

- 주 기**
- 가능상 유해한 BURR 및 WELDLINE 등이 없을 것.
 - 적용 TERMINAL(02511) ; ST731374-3,ST731375-3
적용 TERMINAL(C060) ; ST731411-3,ST731412-3,ST731413-3
적용 CONNECTOR ; MG645941
적용 LEVER; 635752-5
 - 제품내 함유된 6대 유해물질 (납,수은,카드뮴,6가크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.

APPROVED

2021-11-01

KOREA ELECTRIC
TERMINAL CO., LTD.
Korea Electric Te
rminal Co., LTD.

ISSUE MARK

				MATERIAL	SEE TABLE	KET ENGINEERED	KOREA ELECTRIC TERMINAL CO., LTD.
				FINISH	SEE TABLE		
				WIRE RANGE	-	CLASS	HYBRID
				INSULATION	-	TYPE	025060
⚠	검사 성적서 합격에 따른 도면 제작성	SYS	WDH	CMS	20.11.23	PART NO.	MG657202
LTR	REVISION RECORD	DR.	CHK.	APP.	DATE	SCALE	1/1
	DR. SYS 2020.06.25		CHK. WDH 2020.06.25			PART_NAME	025060 68F ASSY_B
	CHK.		APP. CMS 2020.06.25				