



GENERAL TOLERANCE (TERMINAL)					GENERAL TOLERANCE (HOUSING)							USED ON
10MAX	20MAX	45MAX	ANGLE	ECCENT	10MAX	50MAX	100MAX	250MAX	250VR	ANGLE	ECCENT	
±0.2	±0.25	±0.3	±30'	0.1	±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	
GENERAL TOLERANCE (SILICONE RUBBER)												
0 TO 6		6 TO 10		10 TO 18		18 TO 30		30 TO 50		50 TO 80		
±0.4		±0.5		±0.6		±0.8		±1.0		±1.2		

NO	PART NAME	PART NO.	Q'TY	MATERIAL	FINISH
1	BULB HOLDER-DOUBLE	MG 670483-K	1	PBT	GRAY
2	EARTH TERMINAL	P 900467	1	PBP 0.3T	UNPLATE
3	POSITIVE TERMINAL	P 900470	2	PBP 0.3T	UNPLATE
4	INNER SEAL	P 900623	1	SILICONE	RED
5	SEAL GASKET	P 900624	1	SILICONE	GRAY

NOTE

- 1) 치시없는 R은 전부 0.3으로 할 것.
 2) 기밀상 유해한 BURR, 변형등이 없을 것.
 3) 상태 HS'G : SWP 3P PLUG
 KET PART NO. : MG610327
 4) * 표시부의 치수는 참고 치 임.



ISSUE MARK

				MATERIAL	SEE TABLE	KOREA ELECTRIC TERMINAL CO., LTD.
				FINISH	SEE TABLE	
				WIRE RANGE	SEE TABLE	CLASS
				INSULATION	SEE TABLE	TYPE
				SCALE	2/1	PART NO.
				PART NAME	FRT BULB HOLDER SINGLE 3P ASS'Y	